

Relief Valve



A valve used to control gas agent discharge mistakenly when CO₂ cylinder leaks.

Manufacturer	DongSung FINETEC Co.,LTD
Model No.	FTRF-6
Diameter	6A
Working Pressure	0.1~0.3MPa
Material	Brass(KS D 5101 C3604)

Actuating Device



Actuating device to release high pressured gas from CO₂ cylinder by using solenoid valve. The discharged gas opens selection valve and cylinder valve.

Manufacturer	DongSung FINETEC Co.,LTD
Model No.	NK-AD-01 / DS-AD65
Standard	0.65kg/1L, DC-24V
Dimension	320mm(W) x 125mm(D) x 410mm(H)
Material	SSC 13A
accessories and parts	Actuating cylinder, Pressure switch, Solenoid valve

Solenoid Valve



It is an electromechanically operated valve. It activates CO₂ cylinder valve in actuating device.

Manufacturer	DongSung FINETEC Co.,LTD
Model No.	DY-6A-01
Dimension	135mm(W) x 25mm(D) x 103mm(H)
Operating Voltage	DC-24V
Rated Current	1.5A

Modular Control Panel



It controls a manual operation box, smoke & heat detectors, Siren, Solenoid valve and so on.

Manufacturer	DongSung FINETEC Co.,LTD
Model No.	DSCP-01
Dimension	250mm(W) x 85mm(D) x 360mm(H)
Circuit Specification	Single
Rated Current	AC220V/60Hz