

Storage Cylinder



A Mn-Steel container for storing liquefied gas at 15.0 Mpa working pressure. It should be certified by KGS.

Manufacturer	DongSung FINETEC Co.,LTD	
Model No.	FTC-40	FTC-68
Water capacity	40.2ℓ	68ℓ
Out Diameter	232mm	267mm
Length	1,175mm	1,500mm
Test Pressure	25.0MPa	25.0MPa
Working Pressure	15.0MPa	15.0MPa
Color	Gray	Gray
Net weight(Cylinder)	About 45kg	About 75kg
Material	Mn-Steel(KS B 6210)	Mn-Steel(KS B 6210)

Storage Cylinder



A Mn-Steel container for storing liquefied gas at 15.0 Mpa working pressure. It should be certified by KGS.

Manufacturer	DongSung FINETEC Co.,LTD	
Model No.	FTC-83	FTC-125
Water capacity	82.5ℓ	125ℓ
Out Diameter	273mm	356mm
Length	1,710mm	1,540mm
Test Pressure	25.0MPa	25.0MPa
Working Pressure	15.0MPa	15.0MPa
Color	Gray	Gray
Net weight(Cylinder)	About 87kg	About 118.5kg
Material	Mn-Steel(KS B 6210)	Mn-Steel(KS B 6210)

Cylinder Valve



A valve used to release fire extinguishing agent.

Manufacturer	DongSung FINETEC Co.,LTD	
Model No.	FTV-40	
Size	40A	
Test Pressure	11.8MPa	
Working Pressure	7.1MPa	
Safer disc burst Pressure	7.8~9.4MPa	
Material	Brass(KS D 5101 C3771)	

Needle Valve



It activates cylinder valve by breaking Burst Disc.

Manufacturer	DongSung FINETEC Co.,LTD	
Model No.	FTN-40	
Diameter	6A	
Working pressure	1.8MPa	
Material	Brass(KS D 5101 C3771)	